



TECHNICAL DATA issued following the UNI EN 14877 standard

SPORTFLEX SUPER X TRAINING - thickness 13 mm

03/2007

Rolls: height cm 122-160, lenght max 15 mtl. Weight: 11 kg/mq

<u>REQUIREMENTS FOR SAFETY IN USE</u>	<u>TEST METHODS</u>	<u>UNIT OF MEASURE</u>	<u>REQUIREMENTS</u>	<u>AVERAGE VALUES RESULTING FROM PRODUCTION CONTROLS</u>
Slip resistance	UNI EN 13036-4	-	55 ÷ 110	100 (dry) 56 (wet)
Shock absorption	UNI EN 14808	%	35 ÷ 50	39
Vertical deformation	UNI EN 14809	mm	≤ 3	2,2
<u>TECHNICAL PROPERTIES</u>	<u>TEST METHODS</u>	<u>UNIT OF MEASURE</u>	<u>REQUIREMENTS</u>	<u>AVERAGE VALUES RESULTING FROM PRODUCTION CONTROLS</u>
Thickness of surface	UNI EN 1969	mm	≥ 10	13
Water permeability	UNI EN 12616	mm/h	-	impermeable
Resistance to wear	UNI EN ISO 5470-1	mg	≤ 4000	1500
Resistance to artificial weathering	UNI EN 14836	-	manifold	in conformity
Tensile strenght (T _R)	UNI EN 12230	MPa	≥ 0,4	0,6
Elongation to rupture (E _b)	UNI EN 12230	%	≥ 40	170
Spike resistance	UNI EN 14810	%	ΔT _R ≤ 20 ΔE _b ≤ 20	in conformity in conformity
<u>OPTIONAL PROPERTIES</u>	<u>TEST METHODS</u>	<u>UNIT OF MEASURE</u>	<u>REQUIREMENTS</u>	<u>AVERAGE VALUES RESULTING FROM PRODUCTION CONTROLS</u>
Hardness	ISO 7619	Shore A	-	52
Abrasion resistance	ISO 4649 method A 5 N load	mm ³	-	220

Mondo keeps the right to modify the characteristics of the products in any moment.